

MATERIAL SAFETY DATA SHEET

Effective Date: April 4, 2006

Revised: August 31, 2006



713 S Fidalgo Street
Seattle, WA 98108
206-768-3200

EMERGENCY TELEPHONE NO.: 1-800-222-1222
or **Dial 911** American Poison Control Center

SECTION 1 – PRODUCT IDENTIFICATION

| | | | |
|---|------------------------------------|---|--|
| Material Name: GRANITE | | NOT A CONTROLLED PRODUCT | |
| Chemical Family Inorganic Compound | Chemical Formula Mixture | Molecular Weight Not Applicable | |
| Material Use Aggregates | | DOT Identification No. None | |
| Trade Name and Synonyms Natural Stone, Crushed Stone, Rhyolite, Aggregate, Manufactured Sand, Rhyolite, Base, Ballast Screenings, Slab, Tile. | | | |

SECTION 2 – COMPOSITION AND INFORMATION ON INGREDIENTS

| COMPONENTS CHEMICAL NAME | CAS REGISTRY NO. | % by WEIGHT (approximate) | MSHA/OSHA PEL | ACGIH TLV-TWA |
|--|------------------------|---------------------------------|--|-----------------------------|
| Silicon Dioxide*, SiO ₂ | 14808-60-7 | 70.0 – 72.0 | (R) 10 mg/m ³ /(% SiO ₂) [§] | (R) 0.05 mg/m ³ |
| Aluminum Oxide, Al ₂ O ₃ | 1344-28-1 | 13.0 – 15.0 | (T) 15 mg/m ³ , (R) 5 mg/m ³ | # 10 mg/m ³ |
| Potassium Oxide, K ₂ O | 12136-45-7 | 4.0 – 5.0 | Not Evaluated | Not Evaluated |
| Sodium Oxide, Na ₂ O | 1313-59-3 | 3.0 – 4.0 | Not Evaluated | 2 mg/m ³ as NaOH |
| Ferrous Oxide, FeO | 1345-25-1 | 1.0 – 2.0 | Not Evaluated | 5 mg/m ³ |
| Ferric Oxide, Fe ₂ O ₃ | 1309-37-1 | 1.0 – 2.0 | 10 mg/m ³ | 5 mg/m ³ |
| Calcium Oxide, CaO | 1305-78-8 | 1.0 – 2.0 | 5 mg/m ³ | 2 mg/m ³ |
| Magnesium Oxide, MgO | 1309-48-4 | < 1.0 | 15 mg/m ³ | 10 mg/m ³ |

The composition of SiO₂ may be up to 100% crystalline silica. (R) Respirable (T) Total § Crystalline silica is normally measured as respirable dust. The OSHA standard also presents a formula for calculation of the PEL based on total dust: 30 mg/m³ / (% SiO₂ + 2). # Particulate matter containing no asbestos and <1% crystalline silica. OSHA LISTS GRANITE AS A CATEGORY "A" STONE (CONTAINING SILICA IN THE FORM OF SILICA DIOXIDE ALSO KNOWN AS QUARTZ). SILICA-CONTAINING DUST FROM THIS STONE CAN CAUSE SILICOSIS, A RESPIRATORY DISEASE THAT IS TYPICALLY FATAL. CUTTING MUST OCCUR UNDER WATER, AND A RESPIRATOR WORN AS OUTLINED IN SECTION 8. OTHER HAZARDS ARE DUE TO THE EXCESSIVE WEIGHT OF GRANITE. USE CRATES THAT WILL NOT BREAK, AND PALLET RACKS RATED HIGHER THAN THE LOAD BEING STORED FOR TILES. BE AWARE OF UNSECURED STACKS AND BREAKING CRATES. USE PROPER EQUIPMENT TO HANDLE GRANITE SLABS. GRANITE IS A MIXTURE OF NATURAL OCCURRING MINERALS. GRANITE IS PERFECTLY SAFE WHEN PROPERLY INSTALLED.

SECTION 3 – PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Appearance and Odor Solid state, angular, white, green, gray, pink, red to black particles ranging in size from dust to large stones over 6 inches in size. Quartz generally occurs as rounded grains within granite particles, but individual quartz grains may dislodge from granite during handling. Odorless. | Specific Gravity 2.6 – 2.81 |
| Boiling Point Not applicable | Vapor Density in Air (Air = 1) Not applicable |
| Vapor Pressure Not applicable | % Volatile, by Volume 0% |
| Evaporation Rate 0% | Solubility in Water Negligible |

SECTION 4 – STABILITY AND REACTIVITY DATA

| | |
|--|--|
| Stability Stable | Hazardous Polymerization Not known to polymerize |
| Conditions to Avoid Avoid contact with incompatible materials (see below) and exposure to crystalline silica (quartz) dust particles, usually generated while cutting, crushing, sawing, or removing. | |
| Incompatibility (material to avoid) Contact with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride may cause fire and/or explosions. Silica dissolves readily in hydrofluoric acid producing a corrosive gas – silicon tetra fluoride. | |
| Hazardous Decomposition Products These products do not contain asbestos. Under normal conditions these products do not release hazardous materials after installation and are not hazardous waste should disposal be necessary. The main concern would come from inhaling crystalline silica dust release while cutting or removing tiles. | |

SECTION 5 – HAZARDS AND TOXICITY

| |
|---|
| Exposure Limits Below is a definition of exposure limits in the workplace, especially when contact with this product and other chemicals are concurrent. Limits are eight-hour time-weighted averages (TWA), unless specified otherwise. Limits for cristobalite and tridymite (other forms of crystalline silica) are equal to one-half of the limits for quartz. |
| Inhalable Particulate Limits <ul style="list-style-type: none">◆ 2001 ACGIH TLV[®] = 10 mg/m³ (inhalable /total particulate, not otherwise specified)◆ 2001 ACGIH TLV[®] = 3 mg/m³ (respirable particulate, not otherwise specified)◆ OSHA PEL = 15 mg/m³ (total particulate, not otherwise regulated) |

◆ **OSHA PEL = 5 mg/m³ (respirable particulate, not otherwise regulated).**

Respirable Limit, Crystalline Silica (SiO₂ or Quartz)

ACGIH TLV[®] = 0.05 mg/m³, MSHA and OSHA PEL = 10 mg/m³ (%SiO₂ + 2), for respirable dust containing crystalline silica.

Total Dust Limits, Respirable and Nonrespirable

1973 ACGIH TLV[®] = 30 mg/m³ ÷ (% quartz + 3).

MSHA PEL = 10 mg/m³ for nuisance particulates listed in Appendix E of the 1973 ACGIH TLV[®] booklet. [Appendix E includes: aluminum oxide (Al₂O₃); calcium carbonate; cellulose (paper fiber); Portland cement; corundum (Al₂O₃); emery; glass {fibrous (< 5-7 μm in diameter) or dust}; glycerin mist; graphite (synthetic); gypsum; vegetable oil mists (except castor, cashew nut, or similar irritant oils); kaolin; limestone; magnesite; marble; pentacrythritol; plaster of Paris; rouge; silicon carbide; starch; sucrose; tin oxide; and titanium dioxide].

Route of Entry

Skin Contact

Skin Absorption

Eye Contact

Ingestion

Acute Inhalation

Chronic Inhalation

Effects of Acute Exposure to Product

Skin Direct contact may cause irritation by mechanical abrasion. Skin absorption usually is not a significant route of exposure.

Eyes Direct contact may cause eye irritation by mechanical abrasion with discomfort or pain, local redness, and swelling of the conjunctiva may occur.

Inhalation If inhaled in the form of dust, it may cause nose, throat, and respiratory tract irritation by mechanical abrasion. Exposures in excess of appropriate exposure limits may cause coughing, sneezing, and shortness of breath.

Ingestion Expected to be practically non-toxic. If ingested in large quantities, may cause gastro-intestinal irritation and/or blockage.

Acute toxic effects are not a concern in the use of granite for construction purposes.

However, inhaling respirable dust may aggravate existing respiratory system disease(s) and/or dysfunctions. Exposure to dust may aggravate existing skin and or eye conditions.

Effects of Chronic Exposure to Granite Dust

Quartz is a natural constituent of the Earth's crust and does not chemically combine with any other substance. Granite, quartz monzonite, and granodiorite contain 70% to 77% silica. Exposure to silica-containing dust and/or mica-containing dust at any time poses a potential health hazard. Repeated overexposure to very high levels of respirable crystalline silica (quartz, cristobalite, tridymite) for periods of six months or more have caused acute silicosis. Not all individuals with silicosis will exhibit symptoms (signs) of the disease. Acute silicosis is a rapidly progressive, incurable lung disease that is typically fatal. Symptoms can appear at any time, even years after exposure has ceased. Symptoms include (but are not limited to) shortness of breath, diminished work capacity, cough, fever, right heart enlargement and/or failure, weight loss, and chest pain. Excessive inhalation of dust may result in respiratory disease, including silicosis, pneumoconiosis, and pulmonary fibrosis. Persons with silicosis have an increased risk of pulmonary tuberculosis infection. Smoking may increase the risk of developing lung disorders, including emphysema and lung cancer. Test reports show respirable dust containing newly broken silica particles to be more hazardous to animals in laboratory tests than respirable dust containing older silica particles of similar size.

Irritancy of Product

Eyes

Sensitization to Product

None

Synergistic Materials

None reported

SECTION 6 – FIRST AID MEASURES

Eyes

Immediately rinse contaminated eye(s) with gently running lukewarm water (saline solution is preferred) for at least 15 minutes, while holding the eyelid(s) open. In the case of an embedded particle in the eye, or if irritation occurs, consult a physician. Beyond flushing, do not attempt to remove material from the eye(s).

Skin

Carefully and gently, brush the contaminated body surfaces in order to remove all traces of Granite. Use a brush, cloth, or gloves. Remove all contaminated clothing. Wash work clothes after each use. Wash dust-exposed skin with soap and water before eating or drinking. Contact a physician if irritation persists or later develops.

Inhalation

Move source of dust away from person, or move victim to source of fresh air. Dust in throat and nasal passages should clear spontaneously. Obtain medical attention immediately. If victim does not breath, give artificial respiration. Contact a physician immediately.

Ingestion

If victim is conscious, wash out mouth with water. Have conscious person drink several glasses of water. Induce vomiting. Contact a physician immediately. Never give anything by mouth to an unconscious or convulsing person.

General Advice

Consult a physician for all exposures except minor instances of inhalation.

SECTION 7 – REGULATORY INFORMATION

Carcinogenicity Reproductive Effects Teratogenicity Mutagenicity

Granite is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). In October 1996, an IARC Working Group re-assessing crystalline silica, a component of Granite, designated respirable crystalline silica as carcinogenic (Group 1). The NTP's Report on Carcinogens, 9th edition, lists respirable crystalline silica as a "known human carcinogen". In year 2000, the American Conference of Governmental Industrial Hygienists (ACGIH) listed respirable crystalline silica (quartz) as a suspected human carcinogen (A-2). These statements are from sufficient reported evidence of carcinogenicity in certain experimental animals and on selected epidemiological studies of workers exposed to crystalline silica.

CALIFORNIA PROPOSITION 65: WARNING (Safe Drinking Water and Toxic Enforcement Act of 1986)
Component Granite does not appear on the above regulatory listing. However, crystalline silica is a component of this product. California regulates crystalline silica (airborne particles of respirable size) under the state of California Safe Drinking Water and Toxic Enforcement Act of 1986 as a cause of cancer.

CWA 311 – Clean Water Act List of Hazardous Substances

Granite does not appear on the Clean Water Act (CWA) list of hazardous substances.

Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) / The Emergency Planning and "Community Right-to-Know" Act (EPCRA) / Comprehensive Environmental Response, Compensation and Liability Act (CERCLA).

Component Granite has been reviewed against the following regulatory listings:

- ◆ **Section 302 – Emergency Planning Notification. Extremely Hazardous Substances (EHS) List and Threshold Planning Quantity (TPQ). (40 CFR, Part 355, Section 30): Not listed.**
- ◆ **Section 304 – Emergency Release Notification. Extremely Hazardous Substances (EHS) and Reportable Quantity (RQ) List. (40 CFR, Part 355, Section 40): Not listed.**
- ◆ **Section 311/312 – Hazard Categories (40 CFR, Part 370): This product is regulated under CFR 1910.1200 (OSHA Hazard Communication).**
- ◆ **Section 313 – Toxics Release Inventory (TRI). Toxic Chemical List (40 CFR, Part 372): Not listed.**

Transportation – Hazardous Materials Regulations (USA) & Transportation of Dangerous Goods (TDG) Regulations (Can).

Granite does not appear on the above regulatory listings.

Toxic Substances Control Act (TSCA)

All naturally occurring components of this product are automatically included in the USEPA TSCA Inventory List per 40 CFR 710.4 (b). Granite is exempt from reporting under the inventory update rule.

Canadian Environmental Protection Act (CEPA)

Quartz, a component of this product, appears on the Domestic Substances List (DSL).

ANSI/NSF 60 – Drinking Water Treatment Additives.

Not applicable.

FDA – U.S. Food and Drug Administration, Department of Health and Human Services

Not applicable.

SECTION 8 – PREVENTATIVE MEASURES, PERSONAL PROTECTION, AND CONTROLS

Personal Protective Equipment (PPE)



Wear clean, dry gloves, full-length pants over boots, long sleeved shirt buttoned at the neck, head protection, and approved eye protection selected for the working conditions.

Eyes



Wear safety glasses with side shields as minimum protection. Dust goggles should be worn when excessively (visible) dusty conditions are present or are anticipated.

Skin

Clothing, boots, and gloves that fully covers all skin provides the best protection.

Respiratory Protection



- ◆ **Wear a NIOSH approved dust respirator for respirable quartz levels that exceed or are likely to exceed an 8-hr TWA of 0.1 mg/m³.**
- ◆ **Wear a NIOSH approved HEPA filter respirator for respirable quartz levels that exceed or are likely to exceed an 8-hr TWA of 0.5 mg/m³.**
- ◆ **Wear a NIOSH approved positive pressure, full-face respirator, or equivalent if respirable quartz levels exceed or are likely to exceed an 8-hr TWA of 5 mg/m³.**
- ◆ **Respirator use must comply with applicable MSHA or OSHA standards, which include provisions for a user-training program, respirator repair and cleaning, respirator fit testing, and other requirements.**

Hygiene

Wash work clothes after use and dust-exposed skin with soap and water before eating, drinking, smoking, and using toilet facilities. Avoid breathing dust, skin and eye contact.

Engineering Controls

- ◆ **Ventilation: Use local exhaust, general ventilation, or natural ventilation adequate to maintain exposures below appropriate exposure limits.**
- ◆ **Monitor respirable dust and quartz levels regularly.**
- ◆ **Dust and quartz levels in excess of appropriate exposure limits should be reduced by all feasible engineering controls including (but not limited to) wet suppression, ventilation, process enclosure, and enclosed employee work stations.**

SECTION 9 – STORAGE AND HANDLING PRECAUTIONS

Protection

Respirable crystalline silica-containing dust usually appears during processing, cutting, drilling, routing, and removal. Do not breathe dust. Use personal protection and controls identified in Section 8 of this MSDS as appropriate. Avoid contact with skin and eyes.

Storage

Do not store near food and beverages or smoking materials. Shelf life is unlimited.

Handling

This product is not an abrasive blasting medium or for foundry applications. Do not stand on stacked tiles, as they may be unstable. Use appropriate equipment for handling large pieces: fork lift jacks, etc. and follow all safety rules. Store tiles on appropriately strong racks and in crates designed to handle large loads. Store slabs on edge in racks.

SECTION 10 – SPILL OR LEAK CLEANUP AND WASTE DISPOSAL

Material Release or Spill

- ◆ Spilled material where dust occurs, may overexpose cleanup personnel to respirable crystalline silica-containing dust.
- ◆ Use the personal protection and controls identified in Section 8 of this MSDS as appropriate.
- ◆ Wetting of spilled material and/or use of respiratory protective equipment may be necessary.
- ◆ Spilled material must not be dry swept. Use water or a vacuum instead.
- ◆ Prevent spilled material from inadvertently entering streams, drains, or sewers.
- ◆ Train all personnel on handling and safety rules for working with granite, forklifts, sampling, etc. as needed.

Waste Disposal

- ◆ Collect and reuse clean material.
- ◆ Dispose of waste materials in accordance with applicable federal, state, provincial, and local environmental laws and regulations.

SECTION 11 – FIRE AND EXPLOSION HAZARD DATA

Flammable

Yes No

Extinguishing Media

Granite does not burn. Use extinguishing media appropriate to surrounding fire conditions.

Special Fire Fighting Procedures

Granite is generally non-flammable, but ignites on contact with powerful oxidizing agents such as fluorine, boron trifluoride, chlorine trifluoride, manganese trifluoride, and oxygen difluoride. These substances may cause fire and/or explosions. Silica dissolves readily in hydrofluoric acid producing a corrosive gas – silicon tetra fluoride. Wear adequate personal protection to prevent contact with material or its combustion products. Firefighters should use self-contained NIOSH approved breathing apparatus with full-face piece to protect against the products of combustion.

Flash point (°C) and Method
Not applicable

Upper flammable limit
Not applicable

Lower flammable limit
Not applicable

Auto Ignition Temperature (°C)
Not applicable

TDG Flammability Classification
Not applicable

Hazardous Combustion Products
None

Dangerous Combustion Products **None**

EXPLOSION DATA

Sensitivity to Chemical Impact
Not applicable

Rate of Burning
Not applicable

Explosive Power
Not applicable

Sensitivity to Static Discharge
Not applicable

SECTION 12 – TRANSPORT INFORMATION

Dot Hazard Classification – 49 CFR 172.101
Non-Regulated by D.O.T.

Placard Required
None


Label Required
Label as required by the OSHA Hazard Communication standard {29 CFR 1910.1200 (f)}, and applicable state and local regulations.

RQ (Reportable Quantity) – 49 CFR 172.101
Not applicable


MATERIAL IDENTIFICATION SYSTEMS – HAZARD LABELING
 [May be required by the OSHA Hazard Communication standard {29 CFR 1910.1200 (f)}, and applicable state and local regulations]



Hazardous Materials Identification System (U.S.)



National Fire Protection Association (U.S.)
 Where:
 0 = Least 1 = Slight 2 = Moderate
 3 = High 4 = Extreme



D-2A
 Workplace Hazardous Materials Information System (Canada)
 Classification D2A Materials causing other toxic effects

SECTION 13 – GLOSSARY

Agencies and Regulations

ACGIH: American Conference of Government Industrial Hygienists
CFR: US Code of Federal Regulations
DOT: US Department of Transportation
DSL: Domestic Substances List
IARC: International Agency for Research on Cancer
NIOSH: National Institute for Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration, US Department of Labor
SARA: Title III of the Superfund Amendments and Reauthorization Act, 1986

Abbreviations

- ◆ **IDLH:** Immediately Dangerous to Life and Health
- ◆ **mg/m³** = milligrams of substance per cubic meter of air
- ◆ **MSHA PEL** = Permissible Exposure Limit of the Mine Safety and Health Administration (MSHA)
- ◆ **OSHA PEL** = Permissible Exposure Limit of the Occupational Safety and Health Administration (OSHA)
- ◆ **TLV[®]** = Threshold Limit Value of the American Conference of Governmental Industrial Hygienists (ACGIH)
- ◆ **TWA** = Time-Weighted Average

Sources Used

NFPA, TDG, CSST, RSST, (LSRO-FASEB), Hazardous Products Act, Environment Canada, Enviroguide, OSHA, ACGIH, IARC, NIOSH, CFR, NTP, HSDB, EPA SRS, MSHA, Geology of the nonmetals, Health Canada, APAC Inc MSDS, Graymont (QC) Inc MSDS, Martin Marietta Materials MSDS, Marble Institute of America Technical Bulletin "Preparing a Generic MSDS for Natural Stone."

SECTION 14 – PREPARATION OF THIS DOCUMENT

Prepared by

Wayne Bergman, tel: 206-768-3200
Operations Manager
Pental Granite & Marble
713 S Fidalgo Street
Seattle, WA 98108

Other Contacts

Peter Pental, cell: 206-255-6344
Ravi Pental, cell: 206-255-6338

Date of Preparation

April 4, 2006

Updated

August 31, 2006

Notice

Pental Granite & Marble believes the information contained herein is accurate. The suggested precautions and recommendations come from recognized good work practices and experience as of the date of publication. They are not necessarily all-inclusive or fully adequate in every circumstance, as one cannot anticipate all use situations. However, the suggestions should not be confused with nor followed in violation of applicable laws, regulation, rules, insurance requirements, or safety practices. In addition, one must not use product in a manner that could cause harm.

NO WARRANTY IS MADE, EXPRESSED, OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OTHERWISE.